

Level VI

CoC Tier 2

## 18 Watt - Series

Desktop Type

uA19-1XXX

↳ O / P Voltage



### Green Mode

CEC, DoE Level VI, Energy Star, ErP Stage 2, CoC Tier 2, NRCAN & GEMS Level VI  
No Load Power Consumption Less Than 0.075W

### Features :

- 100-240VAC Universal Input
- Single Output to 18W
- Regulated Output With Low Ripple Noise
- Safety Agency Requirements and EMI/EMS Certified
- Modified and Custom Design Available
- 1 Year Warranty

Model	O/P Voltage	O/P Current	Watt
uA19-1005	5.0V	3.00A	15.00W
uA19-1066	5.9V	2.50A	14.75W
uA19-1006A	5.9V	3.00A	17.70W
uA19-1007	7.0V	2.50A	17.50W
uA19-1007A	7.5V	2.50A	18.75W
uA19-1009	9.0V	2.20A	19.80W
uA19-1010	10.0V	1.90A	19.00W
uA19-1011	11.0V	1.60A	17.60W
uA19-1012	12.0V	1.60A	19.20W
uA19-1015	15.0V	1.30A	19.50W
uA19-1016	16.0V	1.20A	19.20W
uA19-1018	18.0V	1.10A	19.80W
uA19-1024	24.0V	0.80A	19.20W

### Input

Voltage	100-240VAC
Line Frequency	50-60Hz
Current	0.48A Max.
Protection	Internal Primary Current Fuse
Configuration	IEC60320/C6,C8,C14

### Output

Load Regulation	±5% ( Typical )
Ripple	2% Vp-p Max. for Output Voltage@ Full Load
Transient Response	0.5mS for 50% Load Change Typical
Hold-up Time	10mS @ Full Load
Protection	Short Circuit Protection / Over Voltage Protection / Over Current Protection
DC Cord	22AWG / 20AWG / 18AWG
Ferrite Core	No (Optional)

### Safety Approvals

CB / UL / cUL / FCC / GS / CE / PSE / BSMI / CCC / RCM / LPS

### Electrical

Topology	Switching Flyback
Dielectric Withstand	3,000 VAC Primary - Secondary
Leakage Current	0.25mA
Efficiency	DoE Level VI, Energy Star, ErP Stage 2, CoC Tier 2, NRCAN & GEMS Level VI Certified
EMI Conduction & Radiation	Compliance to IEC55032 Class B
Harmonic Current	Compliance to EN61000-3-2,3
EMS Immunity	Compliance to EN61000-4-2,3,4,5,6,8,11
MTBF	300,000 Calculated Hours at 25°C, by Telcordia SR-332

### Environmental

Operating Temperature	0 to + 40°C
Storage Temperature	-20 to + 80°C
Relative Humidity	Operating : 20 to 80% RH Storage : 10 to 90% RH
Cooling	Natural Convection Cooling

### Mechanical

Case Dimension	P : L100 x W50 x H33 (mm) A : L88 x W50 x H34 (mm)
Weight	144g (Ref.)

