



Level VI

CoC Tier 2

## 18 Watt Series

Wall Mount Type  
USA / Japan / Taiwan / Europe / UK / Australia /  
China / AC Plug Changeable

WM19 - 1 X X X - Y

O / P Voltage ← X X X → Y  
 U : US Plug / JP Plug  
 E : EU Plug  
 B : UK Plug  
 A : AU Plug  
 C : CN Plug  
 V : Changeable Plug

### Green Mode

CEC, DoE Level VI, Energy Star, ErP Stage 2, CoC Tier 2,  
NRCAN & GEMS Level VI  
No Load Power Consumption Less Than 0.075W

### Features :

- 100-240VAC Universal Input
- Single Output to 18W
- Regulated Output With Low Ripple Noise
- Safety Agency Requirements and EMI/EMS Certified
- Modified and Custom Design Available
- 1 Year Warranty

Model	O/P Voltage	O/P Current	Watt
WM19-1005	5.0V	3.00A	15.00W
WM19-1006	5.9V	2.50A	14.75W
WM19-1006A	5.9V	3.00A	17.70W
WM19-1007	7.0V	2.50A	17.50W
WM19-1007A	7.5V	2.50A	18.75W
WM19-1009	9.0V	2.20A	19.80W
WM19-1010	10.0V	1.90A	19.00W
WM19-1011	11.0V	1.60A	17.60W
WM19-1012	12.0V	1.60A	19.20W
WM19-1015	15.0V	1.30A	19.50W
WM19-1016	16.0V	1.20A	19.20W
WM19-1018	18.0V	1.10A	19.80W
WM19-1024	24.0V	0.80A	19.20W

### Input

Voltage	100-240VAC
Line Frequency	50-60Hz
Current	0.48A Max.
Protection	Internal Primary Current Fuse
Configuration	U for US Plug / JP Plug
	E for EU Plug
	B for UK Plug
	A for AU Plug
	C for CN Plug
V for Changeable Plug	

### Output

Load Regulation	±5% ( Typical )
Ripple	2% Vp-p Max. for Output Voltage@ Full Load
Transient Response	0.5mS for 50% Load Change Typical
Hold-up Time	10mS @ Full Load
Protection	Short Circuit Protection / Over Voltage Protection / Over Current Protection
DC Cord	22AWG / 20AWG / 18AWG
Ferrite Core	No (Optional)

### Safety Approvals

For USA- CB / UL / cUL / FCC / PSE / BSMI / LPS  
 For Europe & UK - CB / CE / GS / LPS  
 For Australia - CB / RCM / LPS  
 For China - CB / CCC / LPS

### Electrical

Topology	Switching Flyback
Dielectric Withstand	3000VAC Primary - Secondary
Leakage Current	0.25mA
Efficiency	DoE Level VI, Energy Star, ErP Stage 2, CoC Tier 2, NRCAN & GEMS Level VI Certified
EMI Conduction & Radiation	Compliance to IEC55032 Class B
Harmonic Current	Compliance to EN61000-3-2,3
EMS Immunity	Compliance to IEC61000-4-2,3,4,5,6,8,11
MTBF	300,000 Calculated Hours at 25°C , by Telcordia SR-332

### Environmental

Operating Temperature	0 to + 40°C
Storage Temperature	-20 to + 80°C
Relative Humidity	Operating : 20 to 80% RH Storage : 10 to 90% RH
Cooling	Natural Convection Cooling

### Mechanical

Case Dimension	U & C - L 72 x W 34 x H 69 (mm)
	E - L 72 x W 34 x H 90 (mm)
	B - L 72 x W 50 x H 81 (mm)
	A - L 72 x W 40 x H 78 (mm)
	V - L 75 x W 36 x H 66 (mm)
Weight	U : 148g      A : 150g
	E : 154g      C : 148g
	V : 158g (Ref.)      B : 158g

