



Level VI

CoC Tier 2

65 Watt Series

Small Size Desktop Type

uA68 - 10XX YY

O / P Voltage ←

→ C6, C14 or C8

Green Mode

CEC, DoE Level VI, Energy Star, ErP Stage 2, CoC Tier 2, NRCAN & GEMS Level VI
No Load Power Consumption Less Than 0.15W

Features :

- Smaller size of 108 x 46 x 32mm
- 100-240VAC Universal Input
- Single Output to 65W
- Regulated Output With Low Ripple Noise
- Safety Agency Requirements and EMI/EMS Certified
- Modified and Custom Design Available
- 1 Year Warranty

Model	O/P Voltage	O/P Current	Watt
uA68-1015	15.0V	4.34A	65W
uA68-1016	16.0V	4.07A	65W
uA68-1018	18.0V	3.62A	65W
uA68-1018A	18.5V	3.52A	65W
uA68-1019	19.0V	3.43A	65W
uA68-1020	20.0V	3.25A	65W
uA68-1024	24.0V	2.71A	65W

Input

Voltage	100-240VAC
Line Frequency	50-60Hz
Current	1.4A Max.
Protection	Internal Primary Current Fuse
Configuration	IEC60320/C6

Output

Load Regulation	±5% (Typical)
Ripple	2% Vp-p Max. for Output Voltage@ Full Load
Transient Response	0.5mS for 50% Load Change Typical
Hold-up Time	10mS @ Full Load
Protection	Short Circuit Protection / Over Voltage Protection / Over Current Protection
DC Cord	18AWG / 16AWG
Ferrite Core	No(Optional)

Safety Approvals

CB / UL / cUL / FCC / GS / CE / PSE / BSMI / LPS

Electrical

Topology	Switching Flyback
Dielectric Withstand	3000VAC Primary - Secondary
Leakage Current	3.5mA @ 3 Pin
Efficiency	DoE Level VI , Energy Star , ErP Stage 2, CoC Tier 2 & NRCAN Certified
EMI Conduction & Radiation	Compliance to IEC55032 Class B
Harmonic Current	Compliance to EN61000-3-2,3
EMS Immunity	Compliance to IEC61000-4-2,3,4,5,6,8,11
MTBF	300,000 Calculated Hours at 25°C , by Telcordia SR-332

Environmental

Operating Temperature	0 to + 40°C
Storage Temperature	-20 to + 80°C
Relative Humidity	Operating : 20 to 80% RH Storage : 10 to 90% RH
Cooling	Natural Convection Cooling

Mechanical

Case Dimension	L 108 x W 46 x H 32 (mm)
Weight	248 g (Ref.)



JET LPS R33154 RoHS